Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-439-6845

Thread Direction:
Right-hand
Thread Length:
Between 4.75 millimeters and 5.25 millimeters
Fastener Length:
Between 20.75 millimeters and 21.25 millimeters
Head Style:
Pan no. 2
Head Diameter:
Between 6.75 millimeters and 7.25 millimeters
Head Height:
Between 3.25 millimeters and 3.75 millimeters
Locking Feature:
Patch threads
First Diameter From Head:
Between 2.94 millimeters and 3.06 millimeters
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
16.0 millimeters
Internal Drive Style:
Cross recess type ii
Thread Diameter:
4.0 millimeters
Thread Pitch In Millimeters:
0.7
External Thread Tolerance Class:
6g
Externally Relieved Body Diameter Quantity:
1
Special Features:
Nylon locking element 6/6 i/a/w I-p-410 to threads
Material:
Steel
Material Specification:
Qq-s-763 cres 300 series military specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 type 2 military specification single treatment response
Thread Series Designator:
M
Shelf Life:
N/a

Externally Relieved Body Screw - Page 2 of 2



Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

spec.