

View Online at <https://aerobasegroup.com/nsn/5305-01-439-6845>

**Thread Direction:**

Right-hand

**Thread Length:**

Between 4.75 millimeters and 5.25 millimeters

**Fastener Length:**

Between 20.75 millimeters and 21.25 millimeters

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 6.75 millimeters and 7.25 millimeters

**Head Height:**

Between 3.25 millimeters and 3.75 millimeters

**Locking Feature:**

Patch threads

**First Diameter From Head:**

Between 2.94 millimeters and 3.06 millimeters

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

16.0 millimeters

**Internal Drive Style:**

Cross recess type ii

**Thread Diameter:**

4.0 millimeters

**Thread Pitch In Millimeters:**

0.7

**External Thread Tolerance Class:**

6g

**Externally Relieved Body Diameter Quantity:**

1

**Special Features:**

Nylon locking element 6/6 i/a/w l-p-410 to threads

**Material:**

Steel

**Material Specification:**

Qq-s-763 cres 300 series military specification single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 type 2 military specification single treatment response

**Thread Series Designator:**

M

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

spec.