## NSN 5305-01-439-7091

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-439-7091 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.350 inches **Fastener Length:** 0.883 inches **Head Style:** Flat countersunk **Head Diameter:** 0.368 inches **Shoulder Diameter:** 0.2485 inches first shoulder and 0.2495 inches first shoulder **Shoulder Length:** 0.070 inches first shoulder **Internal Drive Style:** Hexagon **Thread Diameter:** 0.216 inches Width Across Flats: Between 0.141 inches and 0.143 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 205000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp xm-13 **Material Specification:** Ams 5629 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf

Shelf Life: N/a

## NSN 5305-01-439-7091

Shoulder Screw - Page 2 of 2



	Of			

--

Demilitarization:

No

Fiig:

A003b0