## NSN 5305-01-439-9693

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-439-9693 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 1.048 inches and 1.078 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.688 inches and 0.755 inches **Grip Diameter:** Between 0.3110 inches and 0.3115 inches **Internal Drive Style:** Cross recess type iii **Thread Diameter:** 0.312 inches **Grip Length:** Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch Minimum Yield Strength: 95000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjc **Specification Data:** 80205-nas8805 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

No

**Demilitarization:** 

## NSN 5305-01-439-9693

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0