## NSN 5305-01-440-1819

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-440-1819 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.453 inches **Fastener Length:** Between 1.438 inches and 1.468 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.832 inches and 0.890 inches **Grip Diameter:** Between 0.4360 inches and 0.4370 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.438 inches **Grip Length:** Between 0.990 inches and 1.010 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ams5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1157 professional/industrial association standard Shelf Life: N/a **Unit Of Measure:** 

--

## NSN 5305-01-440-1819

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0