

View Online at <https://aerobasegroup.com/nsn/5305-01-441-7458>

**Fastener Length:**

Between 1.940 inches and 2.000 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.244 inches and 0.279 inches

**Internal Drive Style:**

Cross recess type iii

**Nonmachine Thread Style:**

Wood screw (type wd)

**Countersink Angle:**

Between 80.0 degrees and 82.0 degrees

**Nonmachine Thread Diameter:**

0.138 inches

**Material:**

Steel comp 1010 or steel comp 1012 or steel comp 1013 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1108 or steel comp 1109 or steel comp 1110 or steel comp 1116 or steel comp 1117 or steel comp 1118

**Surface Treatment:**

Cadmium and chromate or zinc and chromate

**Surface Treatment Specification:**

Qq-p-416, type 2, class 3, jdbmil-c-81562, type 2, class 3 federal specification 1st treatment response or qq-z-325, type 2, class 3 federal specification 2nd treatment response or mil-c-81562, type 2, class 3 military specification 2nd treatment response

**Specification Or Standard:**

1 type and 2c style

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-c-81562 spec.