

View Online at <https://aerobasegroup.com/nsn/5305-01-441-8420>

Thread Class:

2a

Thread Direction:

Right-hand

Thread Length:

Between 0.240 inches and 0.260 inches

Fastener Length:

Between 0.610 inches and 0.640 inches

Head Style:

Pan no. 2

Head Diameter:

Between 0.358 inches and 0.373 inches

Head Height:

Between 0.099 inches and 0.110 inches

First Diameter From Head:

Between 0.125 inches and 0.135 inches

Distance From Largest Bearing Surface Of Head To End Of First Diameter:

Between 0.365 inches and 0.385 inches

Internal Drive Style:

Slot

Thread Diameter:

0.190 inches

Thready Qty Per Inch (tpi):

32

Criticality Code Justification:

Zzzy

Externally Relieved Body Diameter Quantity:

1

Material:

Steel comp 303

Material Specification:

Qq-s-764 federal specification single material response

Surface Treatment:

Passivate

Special Test Features:

Special quality control testing

Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

Test Data Document:

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unf

Departure From Cited Document:

As modified by material

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0