

View Online at <https://aerobasegroup.com/nsn/5305-01-441-8420>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.240 inches and 0.260 inches

**Fastener Length:**

Between 0.610 inches and 0.640 inches

**Head Style:**

Pan no. 2

**Head Diameter:**

Between 0.358 inches and 0.373 inches

**Head Height:**

Between 0.099 inches and 0.110 inches

**First Diameter From Head:**

Between 0.125 inches and 0.135 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.365 inches and 0.385 inches

**Internal Drive Style:**

Slot

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

32

**Criticality Code Justification:**

Zzzy

**Externally Relieved Body Diameter Quantity:**

1

**Material:**

Steel comp 303

**Material Specification:**

Qq-s-764 federal specification single material response

**Surface Treatment:**

Passivate

**Special Test Features:**

Special quality control testing

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Test Data Document:**

81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Thread Series Designator:**

Unf

**Departure From Cited Document:**

As modified by material

**Reference Number Differentiating Characteristics:**

As differentiated by material which must conform to ships parts control center special quality control provisions

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0