

View Online at <https://aerobasegroup.com/nsn/5305-01-441-9376>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

Between 0.655 inches and 0.665 inches

**Fastener Length:**

0.750 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.357 inches and 0.373 inches

**Head Height:**

Between 0.122 inches and 0.133 inches

**Internal Drive Style:**

Torx

**Thread Diameter:**

0.190 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

60000 pounds per square inch

**Hardness Rating:**

Between 70.0 rockwell b and 100.0 rockwell b

**Screw Material:**

Steel comp 1010 or steel comp 1020

**Screw Material Specification:**

Sae1010 assn standard 1st material response or sae1020 assn standard 2nd material response

**Screw Surface Treatment:**

Zinc and wax

**Screw Surface Treatment Specification:**

49-00005-403 type 3 cl 3 cage 64678 mfr ref 1st treatment response

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A500d0