NSN 5305-01-441-9789

Machine Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-441-9789

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 1.938 inches and 2.000 inches
Fastener Length:
Between 1.938 inches and 2.000 inches
Head Style:
Pan
Head Diameter:
Between 0.7160 inches and 0.7400 inches
Head Height:
Between 0.2440 inches and 0.2610 inches
Internal Drive Style:
Cross recess type 1
Thread Diameter:
0.375 inches
Thready Qty Per Inch (tpi):
16
Screw Material:
Oorcw material.
Steel
Steel
Steel Screw Material Specification:
Steel Screw Material Specification: Ff-s-92 military specification single material response
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment:
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification:
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response Thread Series Designator:
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response Thread Series Designator: Unc
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response Thread Series Designator: Unc Shelf Life:
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure:
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization:
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No
Steel Screw Material Specification: Ff-s-92 military specification single material response Screw Surface Treatment: Cadmium Screw Surface Treatment Specification: A qq-p-416 ty2 cl3 military specification single treatment response Thread Series Designator: Unc Shelf Life: N/a Unit Of Measure: Demilitarization: No Fiig: