Hexagon Head Cap Screw - Page 1 of 1

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5305-01-441-9794

| Thread Class:2aThread Direction:Right-handThread Length:1.250 inchesFastener Length:2.250 inchesHead Style:Head Style:Head Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesLocking Feature:Patch threads or pellet threads or strip threadsThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80.000 pounds per square inchHardness Rating:80.0 rockwell b fastenerMinimum Yield Strength:40000 pounds per square inchMaterial:Plastic polyamide locking featurePlastic polyamide locking featurePlastic polyamide locking featureMaterial Specification:  |
|---|
| Thread Direction:Right-handThread Length:1.250 inchesFastener Length:2.250 inchesHead Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesLocking Feature:Patch threads or pellet threads or strip threadsThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell b fastenerMinimum Yield Strength:40000 pounds per square inchMaterial:Plastic polyamide locking featurePlastic polyamide locking featureMaterial Specification:   |
| Right-handThread Length:1.250 inchesFastener Length:2.250 inchesHead Style:Head Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesLocking Feature:Patch threads or pellet threads or strip threadsThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell b fastenerMinimum Yield Strength:40000 pounds per square inchMaterial:Plastic polyamide locking featurePlastic polyamide locking featureMaterial Specification:   |
| Thread Length:<br>1.250 inches<br>Fastener Length:<br>2.250 inches<br>Head Style:<br>Head Style:<br>Hexagon<br>Head Height:<br>Between 0.302 inches and 0.323 inches<br>Width Between Flats:<br>Between 0.736 inches and 0.750 inches<br>Locking Feature:<br>Patch threads or pellet threads or strip threads<br>Thread Diameter:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>13<br>Min. Tensile Strength (psi):<br>80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:  |
| <ul> <li>1.250 inches</li> <li>Fastener Length:</li> <li>2.250 inches</li> <li>Head Style:</li> <li>Hexagon</li> <li>Head Height:</li> <li>Between 0.302 inches and 0.323 inches</li> <li>Width Between Flats:</li> <li>Between 0.736 inches and 0.750 inches</li> <li>Locking Feature:</li> <li>Patch threads or pellet threads or strip threads</li> <li>Thread Diameter:</li> <li>0.500 inches</li> <li>Thready Qty Per Inch (tpi):</li> <li>13</li> <li>Min. Tensile Strength (psi):</li> <li>80000 pounds per square inch</li> <li>Hardness Rating:</li> <li>80.0 rockwell b fastener</li> <li>Minimum Yield Strength:</li> <li>40000 pounds per square inch</li> <li>Material:</li> <li>Plastic polyamide locking feature</li> <li>Material Specification:</li> </ul> |
| Fastener Length:2.250 inchesHead Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesLocking Feature:Patch threads or pellet threads or strip threadsThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell b fastenerMinimum Yield Strength:40000 pounds per square inchMaterial:Plastic polyamide locking featureMaterial Specification:   |
| 2.250 inches Head Style: Hexagon Head Height: Between 0.302 inches and 0.323 inches Width Between Flats: Between 0.736 inches and 0.750 inches Locking Feature: Patch threads or pellet threads or strip threads Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b fastener Minimum Yield Strength: 40000 pounds per square inch Material: Plastic polyamide locking feature  |
| Head Style:HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesLocking Feature:Patch threads or pellet threads or strip threadsThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell b fastenerMinimum Yield Strength:40000 pounds per square inchMaterial:Plastic polyamide locking featureMaterial Specification:   |
| HexagonHead Height:Between 0.302 inches and 0.323 inchesWidth Between Flats:Between 0.736 inches and 0.750 inchesLocking Feature:Patch threads or pellet threads or strip threadsThread Diameter:0.500 inchesThready Qty Per Inch (tpi):13Min. Tensile Strength (psi):80000 pounds per square inchHardness Rating:80.0 rockwell b fastenerMinimum Yield Strength:40000 pounds per square inchPlastic polyamide locking featurePlastic polyamide locking featureMaterial:Plastic polyamide locking featureMaterial Specification:  |
| Head Height:<br>Between 0.302 inches and 0.323 inches<br>Width Between Flats:<br>Between 0.736 inches and 0.750 inches<br>Locking Feature:<br>Patch threads or pellet threads or strip threads<br>Thread Diameter:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>13<br>Min. Tensile Strength (psi):<br>80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:   |
| Between 0.302 inches and 0.323 inches<br>Width Between Flats:<br>Between 0.736 inches and 0.750 inches<br>Locking Feature:<br>Patch threads or pellet threads or strip threads<br>Thread Diameter:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>13<br>Min. Tensile Strength (psi):<br>80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:   |
| Width Between Flats: Between 0.736 inches and 0.750 inches Locking Feature: Patch threads or pellet threads or strip threads Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b fastener Minimum Yield Strength: 40000 pounds per square inch Harterial: Plastic polyamide locking feature Material Specification:   |
| Between 0.736 inches and 0.750 inches<br>Locking Feature:<br>Patch threads or pellet threads or strip threads<br>Thread Diameter:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>13<br>Min. Tensile Strength (psi):<br>80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:  |
| Locking Feature:<br>Patch threads or pellet threads or strip threads<br>Thread Diameter:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>13<br>Min. Tensile Strength (psi):<br>80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:   |
| Patch threads or pellet threads or strip threads Thread Diameter: 0.500 inches Thready Qty Per Inch (tpi): 13 Min. Tensile Strength (psi): 80000 pounds per square inch Hardness Rating: 80.0 rockwell b fastener Minimum Yield Strength: 40000 pounds per square inch Material: Plastic polyamide locking feature Material Specification:  |
| Thread Diameter:<br>0.500 inches<br>Thready Qty Per Inch (tpi):<br>13<br>Min. Tensile Strength (psi):<br>80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:   |
| 0.500 inches<br>Thready Qty Per Inch (tpi):<br>13<br>Min. Tensile Strength (psi):<br>80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:   |
| Thready Qty Per Inch (tpi):<br>13<br>Min. Tensile Strength (psi):<br>80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:   |
| <ul> <li>13</li> <li>Min. Tensile Strength (psi):</li> <li>80000 pounds per square inch</li> <li>Hardness Rating:</li> <li>80.0 rockwell b fastener</li> <li>Minimum Yield Strength:</li> <li>40000 pounds per square inch</li> <li>Material:</li> <li>Plastic polyamide locking feature</li> <li>Material Specification:</li> </ul>  |
| Min. Tensile Strength (psi):<br>80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:  |
| 80000 pounds per square inch<br>Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:  |
| Hardness Rating:<br>80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:  |
| 80.0 rockwell b fastener<br>Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:  |
| Minimum Yield Strength:<br>40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:  |
| 40000 pounds per square inch<br>Material:<br>Plastic polyamide locking feature<br>Material Specification:   |
| Material:<br>Plastic polyamide locking feature<br>Material Specification:   |
| Plastic polyamide locking feature Material Specification:   |
| Material Specification:   |
| -   |
|   |
| Qq-n-281 federal specification single material response fastener  |
| Thread Series Designator:   |
| Unc   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A003b0  |
|   |