NSN 5305-01-442-6183

Machine Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-442-6183

Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.313 inches
Fastener Length:
Between 0.313 inches and 0.375 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.322 inches and 0.385 inches
Internal Drive Style:
Torque set
Thread Diameter:
0.190 inches
Thready Qty Per Inch (tpi):
32
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
Between 99.0 degrees and 101.0 degrees
Screw Material:
Titanium alloy uns r56400
Locking Feature Material:
Plastic polychlorotrifluoroethylene
Screw Material Specification:
Ams 4928 assn standard single material response or ams4967 assn standard single material response
Locking Feature Material Specification:
Ams 3650 assn standard single material response
Bearing Surface Of Head Surface Finish:
32.0 microinches
Shank Surface Finish:
32.0 microinches
Thread Surface Finish:
32.0 microinches
Thread Series Designator:
Unjf
Specification Data:
80205-nas1189 professional/industrial association standard
Shelf Life:
N/a

NSN 5305-01-442-6183

Machine Screw - Page 2 of 2



	• •				
In	18	<i>(</i>)+	МЛО	201	ure:

--

Demilitarization:

No

Fiig:

A500d0