Externally Relieved Body Screw - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5305-01-443-3720

| Thread Class: |
|---|
| 2a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| 0.219 inches |
| |
| Fastener Length: Between 0.589 inches and 0.604 inches |
| |
| Head Style: Flat fillister |
| Head Diameter: |
| 0.281 inches |
| |
| Head Height: 0.047 inches |
| |
| First Diameter From Head: Between 0.090 inches and 0.095 inches |
| |
| Distance From Largest Bearing Surface Of Head To End Of First Diameter: |
| Between 0.370 inches and 0.375 inches |
| Internal Drive Style: |
| Slot |
| Thread Diameter: |
| 0.138 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Externally Relieved Body Diameter Quantity: |
| 1 |
| Material: |
| Steel comp 203ez or steel comp 303 or steel comp 303ma or steel comp 303 plus x |
| Surface Treatment: |
| Passivate |
| Thread Series Designator: |
| Unc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A003b0 |
| |
| |