NSN 5305-01-443-6689



Externally Relieved Body Screw - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5305-01-443-6689 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 1.375 inches **Head Style:** Hexagon **Head Height:** 0.156 inches Width Between Flats: 0.437 inches **First Diameter From Head:** Between 0.190 inches and 0.200 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.000 inches **Internal Drive Style:** W/o internal drive **Thread Diameter:** 0.250 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity:** Material: Steel comp 630 **Surface Treatment: Passivate Special Test Features:** Special quality control testing **Test Data Document:** 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc

Departure From Cited Document:

As modified by material

Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

NSN 5305-01-443-6689

Externally Relieved Body Screw - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0