

View Online at <https://aerobasegroup.com/nsn/5305-01-443-7529>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.621 inches

**Fastener Length:**

1.496 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

0.5149 inches

**Head Height:**

0.081 inches

**Grip Diameter:**

Between 0.3735 inches and 0.3745 inches

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.375 inches

**Grip Length:**

0.562 inches

**Thready Qty Per Inch (tpi):**

24

**Min. Tensile Strength (psi):**

160000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Material:**

Steel comp 4140 or steel comp 4340 or steel comp 8740

**Material Specification:**

Mil-s-5626 military specification single material response or mil-s-5000 military specification single material response or mil-s-6049 military specification single material response

**Surface Treatment:**

Cadmium

**Surface Treatment Specification:**

Qq-p-416, ty2, cl2 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0

**Mil-std (military Standard):**

Mil-s-5626 spec.