Socket Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-443-8061

| Thread Class: | lass: | Cla | read | Th |
|---------------|-------|-----|------|----|
|---------------|-------|-----|------|----|

3a

Thread Direction:

**Right-hand** 

# Thread Length:

1.500 inches

### Fastener Length:

5.000 inches

#### Head Style:

Flat chamfer

Head Diameter:

Between 0.735 inches and 0.750 inches

### Head Height:

Between 0.492 inches and 0.500 inches

### Internal Drive Style:

Hexagon

#### Thread Diameter:

0.500 inches

### Width Across Flats:

0.375 inches

# Thready Qty Per Inch (tpi):

13

### Min. Tensile Strength (psi):

80000 pounds per square inch

### Hardness Rating:

80.0 rockwell b

### **Minimum Yield Strength:**

30000 pounds per square inch

### Material:

Steel comp 302 or steel comp 304 or steel comp 305 or steel comp 316 or steel comp 384 or steel comp xm-7

### Material Specification:

Astm a493 assn standard all material responses

#### Surface Treatment:

Passivate

### Surface Treatment Specification:

Qq-p-35 federal specification single treatment response

# **Thread Series Designator:**

Unc

# Shelf Life:

N/a

#### Unit Of Measure:

---

# NSN 5305-01-443-8061

Socket Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

