## NSN 5305-01-443-9716

Close Tolerance Screw - Page 1 of 2



view Online at https://aerobasegroup.com/hsh/5305-01-443-9716
Thread Class:
3a
Thread Direction:
Right-hand
Thread Length:
0.403 inches
Fastener Length:
Between 3.138 inches and 3.168 inches
Head Style:
Flat countersunk
Head Diameter:
Between 0.464 inches and 0.507 inches
Grip Diameter:
Between 0.2490 inches and 0.2495 inches
Internal Drive Style:
Torque-set ribbed
Thread Diameter:
0.250 inches
Grip Length:
Between 2.740 inches and 2.760 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
160000 pounds per square inch
Countersink Angle:
99.0 degrees and 101.0 degrees
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5732 assn standard single material response or ams 5737 assn standard single
material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:
Unjf
Specification Data:
80205-nas1580 professional/industrial association standard
Shelf Life:
N/a
Unit Of Measure:

## NSN 5305-01-443-9716

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0