NSN 5305-01-444-4204

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-444-4204

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
0.240 inches
Fastener Length:
0.880 inches
Head Style:
Pan
Head Diameter:
Between 0.205 inches and 0.219 inches
Head Height:
Between 0.070 inches and 0.080 inches
Shoulder Diameter:
0.076 inches grip and 0.082 inches grip
Shoulder Length:
0.640 inches grip
Internal Drive Style:
Cross recess type 1
End Application:
F-15i
Thread Diameter:
0.112 inches
Thready Qty Per Inch (tpi):
40
Min. Tensile Strength (psi):
80000 pounds per square inch
Shoulder Shape:
Round grip
Special Features:
Altered item from ms51957-20, item is threaded under head 0.240 in., unthreaded portion past the threaded part is 0.640 in.
Material:
Stainless steel
Material Specification:
Qq-s-763 assn standard single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 federal specification single treatment response
Thread Series Designator:

Unc

NSN 5305-01-444-4204

Shoulder Screw - Page 2 of 2



_					
c	hο	JIF.		.ife:	
J	116		_	.II C.	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0