NSN 5305-01-444-6158

Externally Relieved Body Screw - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-444-6158



Thread Class: За **Thread Direction:** Right-hand Thread Length: 0.250 inches **Fastener Length:** 1.000 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.176 inches and 0.183 inches **Head Height:** Between 0.108 inches and 0.112 inches **First Diameter From Head:** Between 0.078 inches and 0.082 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.125 inches **Internal Drive Style:** Hexagon **End Application:** F-15i **Thread Diameter:** 0.112 inches Width Across Flats: Between 0.937 inches and 0.957 inches Thready Qty Per Inch (tpi): 40 Min. Tensile Strength (psi): 160000 pounds per square inch **Hardness Rating:** 33.0 rockwell c and 42.0 rockwell c Minimum Yield Strength: 120000 pounds per square inch **Externally Relieved Body Diameter Quantity: Special Features:** Altered item Material: Iron alloy 660 **Material Specification:** Ams5731 assn standard 1st material response or ams5737 assn standard 2nd material response

NSN 5305-01-444-6158

Externally Relieved Body Screw - Page 2 of 2



| Surface Treatment: |
|--|
| Passivate |
| Surface Treatment Specification: |
| Qq-p-35, type ii federal specification single treatment response |
| Thread Series Designator: |
| Unrc |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |

A003b0