## NSN 5305-01-445-4072

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-445-4072

Thread Class:
2a
Thread Direction:
Right-hand
Thread Length:
Between 0.203 inches and 0.218 inches
Fastener Length:
Between 0.735 inches and 0.765 inches
Head Style:
Knurled no. 4
Head Diameter:
Between 0.312 inches and 0.327 inches
Head Height:
Between 0.302 inches and 0.322 inches
First Diameter From Head:
Between 0.115 inches and 0.125 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
Between 0.428 inches and 0.448 inches
Internal Drive Style:
Slot
Thread Diameter:
0.164 inches
Thready Qty Per Inch (tpi):
32
Criticality Code Justification:
Zzzy
Externally Relieved Body Diameter Quantity:
1
Special Features:
Item must comply with requirements of defense supply center columbus production standard no. Lo1505
Material:
Steel comp 303
Material Specification:
Qq-s-764 federal specification single material response
Surface Treatment:
Passivate
Special Test Features:
Special quality control testing
Test Data Document:
81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Unc

**Thread Series Designator:** 

## NSN 5305-01-445-4072

Externally Relieved Body Screw - Page 2 of 2



Departure	From	Cited	<b>Document:</b>
Departure		Oitcu	Document.

As modified by material

**Reference Number Differentiating Characteristics:** 

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0