NSN 5305-01-445-4085

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-445-4085 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.208 inches and 0.228 inches **Fastener Length:** Between 0.610 inches and 0.640 inches **Head Style:** Pan no. 2 **Head Diameter:** Between 0.213 inches and 0.228 inches **Head Height:** Between 0.127 inches and 0.132 inches **First Diameter From Head:** Between 0.090 inches and 0.100 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.396 inches and 0.416 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Criticality Code Justification:** Zzzy **Externally Relieved Body Diameter Quantity:** Material: Steel comp 303 **Material Specification:** Qq-s-764 federal specification single material response **Surface Treatment: Passivate Special Test Features:** Special quality control testing **Test Data Document:** 81349-mil-p-23199 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Thread Series Designator:**

Departure From Cited Document:

As modified by material

Unc

NSN 5305-01-445-4085

Externally Relieved Body Screw - Page 2 of 2



Reference Number Differentiating Characteristics:

As differentiated by material which must conform to ships parts control center special quality control provisions

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0