NSN 5305-01-445-8300

Close Tolerance Screw - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5305-01-445-8300 |
|---|
| Thread Class: |
| 3a |
| Thread Direction: |
| Right-hand |
| Thread Length: |
| Between 0.337 inches and 0.387 inches |
| Fastener Length: |
| Between 0.534 inches and 0.564 inches |
| Head Style: |
| Pan no. 2 |
| Head Diameter: |
| Between 0.360 inches and 0.374 inches |
| Head Height: |
| Between 0.115 inches and 0.125 inches |
| Grip Diameter: |
| Between 0.1885 inches and 0.1895 inches |
| Internal Drive Style: |
| High-torque |
| Thread Diameter: |
| 0.190 inches |
| Grip Length: |
| Between 0.177 inches and 0.197 inches |
| Thready Qty Per Inch (tpi): |
| 32 |
| Min. Tensile Strength (psi): |
| 160000 pounds per square inch |
| Product Name: |
| Navy special project |
| Material: |
| Iron alloy 660 |
| Material Specification: |
| Ams5731 assn standard single material response or 5732 assn standard single material response or 5737 assn standard single material |
| response or 5853 assn standard single material response |
| Surface Treatment: |
| Cadmium |
| Surface Treatment Specification: |
| Qq-p-416, ty2, cl2 federal specification single treatment response |
| Thread Series Designator: |
| Unjf |
| Shelf Life: |
| N/a |
| Unit Of Measure: |

NSN 5305-01-445-8300

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0