## NSN 5305-01-445-8804

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-445-8804

3a         Firead Direction:         Right-hand         Firead Length:         0.438 inches         Fastener Length:         Between 0.898 inches and 1.015 inches         Head Syte:         Flat countersunk         Head Dimeter:         Between 0.577 inches and 0.635 inches         Grip Length:         Between 0.577 inches and 0.3120 inches         Internal Drive Style:         Torque-set inbed         Torque-set inbed         Thread Diameter:         0.312 inches         0.312 inches         7 Fired Diameter:         0.312 inches         1 Fired Diameter:         0 Fired Diameter:         0 Fired Diameter:         1 Fired Diameter         1 Group Out on (tp():         1 Gausen Diameter (psi):         1 Gausen Diameter (psi):         1 Gaustrang (tp ):	Thread Class:
Right-hand         Firead Length:         0.438 inches         Fastener Length:         Between 0.986 inches and 1.015 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.577 inches and 0.635 inches         Grip Diameter:         Between 0.3110 inches and 0.120 inches         Internal Drive Style:         Torque-set ribbed         Thread Diameter:         0.312 inches         Grip Length:         Between 0.552 inches and 0.572 inches         Thread Vig Per Inch (tpi):         24         Min. Tensile Strength (psi):         18000 pounds per square inch         Coutersink Angle:         Between 0.99.0 degrees and 101.0 degrees         Material:         Ion alloy 660         Material:         Passivate         Surface Treatment:         Pays-36 federal specification:         Quep-36 federal specification:         Quep-36 federal specification:         Pays-36 federal specification single treatment response         Thread Super Superice         Dirater Teatment:         Pays-36 federal specification single treatment response         Surface Treatment:<	3a
Tread Length:         0.438 inches         Fastener Length:         Between 0.985 inches and 1.015 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.577 inches and 0.635 inches         Grip Diameter:         Between 0.571 inches and 0.3120 inches         Internal Drive Style:         Torque-set ribbed         Thread Diameter:         0.312 inches         Grip Length:         1.312 inches         Between 0.552 inches and 0.572 inches         Thready Oty Per Inch (tpi):         24         1.3000 pounds per square inch         Between 9.552 inches and 0.572 inches         Thready Oty Per Inch (tpi):         1.3000 pounds per square inch         Decomersink Angle:         1.3000 pounds per square inch         Between 9.50 degrees and 10.0 degrees         Material         Point Point (tpi):         1.3000 pounds per square inch         Between 9.51 dass standard single material response or ams 5737 assn standard single material response         Strice Treatment Specification:         Qap-25 federal specification single treatment response         Strice Treatment Specification         Qap-25 federal spe	Thread Direction:
Tread Length:         0.438 inches         Fastener Length:         Between 0.985 inches and 1.015 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.577 inches and 0.635 inches         Grip Diameter:         Between 0.571 inches and 0.3120 inches         Internal Drive Style:         Torque-set ribbed         Thread Diameter:         0.312 inches         Grip Length:         1.312 inches         Between 0.552 inches and 0.572 inches         Thready Oty Per Inch (tpi):         24         1.3000 pounds per square inch         Between 9.552 inches and 0.572 inches         Thready Oty Per Inch (tpi):         1.3000 pounds per square inch         Decomersink Angle:         1.3000 pounds per square inch         Between 9.50 degrees and 10.0 degrees         Material         Point Point (tpi):         1.3000 pounds per square inch         Between 9.51 dass standard single material response or ams 5737 assn standard single material response         Strice Treatment Specification:         Qap-25 federal specification single treatment response         Strice Treatment Specification         Qap-25 federal spe	Right-hand
0.438 inchesFastener Length:Between 0.985 inches and 1.015 inchesHead Style:Flat countersunkHead Diameter:Between 0.577 inches and 0.635 inchesGrip Diameter:Between 0.3110 inches and 0.3120 inchesInternal Drive Style:Torque-set ribbedThread Diameter:0.312 inchesBetween 0.552 inches and 0.572 inchesTrip Length:24Between 0.552 inches and 0.572 inchesThread Val Per Inch (tpl):24Botopounds per square inchCountersink Angle:Isotopounds per square inchCountersink Angle:Ion alloy 660MaterialArsof 37 assn standard single material response or ams 5737 assn standard single material responseSurface Treatments:Qay-35 florents pecification:Qay-35 florents pecification single treatment responseChread Stries Designato:UnifSpecification Data:Botopounds per square indate responseSurface Treatment Specification single treatment responseSurface Treatment Specification single treatment responseChread Specification single treatment responseSurface Treatment Specification single treatment responseChread Specification single treatment responseSurface Treatment Specification single treatment responseSurface Tre	-
Fastener Length:         Between 0.985 inches and 1.015 inches         Head Style:         Flat countersunk         Head Diameter:         Between 0.577 inches and 0.635 inches         Grip Diameter:         Between 0.3110 inches and 0.3120 inches         Intread Drive Style:         Torque-set ribbed         Thread Diameter:         0.312 inches         Grip Length:         Between 0.552 inches and 0.572 inches         Thready Daty Per Inch (tpi):         24         Min Tensile Strength (psi):         180000 pounds per square inch         Countersink Angle:         Between 9.0 degrees and 10.0 degrees         Material:         In alloy 660         Strates Standard single material response or ams 5737 assn standard single material response         Strates Treatment:         Paysivale         Gurder Treatment Specification:         Que-Jo Steleral specification single treatment response         Thread Stries Designator:         Unif         Specification Data:         Bottorian Data:         Data Standard specification single treatment response         Strates Specification single treatment response         Strates Designator: <td>-</td>	-
Action of the set of the	Fastener Length:
Flat countersunk         Head Diameter:         Between 0.577 inches and 0.635 inches         Grip Diameter:         Between 0.3110 inches and 0.3120 inches         Internal Drive Style:         Torque-set ribbed         Datameter:         0.312 inches         Grip Length:         Between 0.552 inches and 0.572 inches         Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Material:         Iron alloy 660         Surface Treatment:         Passivate         Surface Treatment         Passivate         Duries Strength (psi):         Iron alloy 660         Material Specification:         Quep-36 Idearal specification single treatment response or ams 5737 assn standard single material response         Surface Treatment:         Passivate         Quep-36 Idearal specification single treatment response         Thread Series Designator:         Unjf         Surface Treatment Specification         Surface Treatment Specification single treatment response         Dread Series D	-
Head Diameter:         Between 0.577 inches and 0.635 inches         Grip Diameter:         Between 0.3110 inches and 0.3120 inches         Internal Drive Style:         Torque-set ribbed         Thread Diameter:         0.312 inches         Grip Length:         Between 0.552 inches and 0.572 inches         Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Material:         Iron alloy 660         Surface Treatment:         Passivate         Surface Treatment:         Passivate         Duries Length Strength (psi):         10000 points per square inch         Diron alloy 660         Material:         Promating Strength (psi):         Ams 5731 assn standard single material response or ams 5737 assn standard single material response         Surface Treatment:         Passivate         Qu-p-35 federal specification:         Qu-p-35 federal specification single treatment response         Thread Series Designator:         Unif         Specification Data: <tr< td=""><td>Head Style:</td></tr<>	Head Style:
Between 0.577 inches and 0.635 inches         Grip Diameter:         Between 0.3110 inches and 0.3120 inches         Internal Drive Style:         Torque-set ribbed         Thread Diameter:         0.312 inches         Grip Length:         Between 0.552 inches and 0.572 inches         Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Material:         Ironaloy 660         Material Specification:         Ars 5731 assn standard single material response or ams 5737 assn standard single material response         Surface Treatment:         Passivate         Gurdpe-35 federal specification:         Qrap-35 federal specification single treatment response         Thread Series Designator:         Unjf         Specification Data:         80205-nas2835 professional/industrial association standard	Flat countersunk
Grip Diameter:Between 0.3110 inches and 0.3120 inchesInternal Drive Style:Torque-set ribbedThread Diameter:0.312 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):10300 pounds per square inchCoutersink Angle:Between 9.0 degrees and 101.0 degreesMaterial:In aloy 660Straft Specification:Aust Systal asen standard single material response or ams 5737 asen standard single material responsePassivateCurter Internet Specification:Aug-35 federal specification single treatment responseThread Series Designator:LingtSpecification Data:Botto Data:	Head Diameter:
Arrenal Drive Style:         Torque-set ribbed         Thread Diameter:         0.312 inches         Grip Length:         Between 0.552 inches and 0.572 inches         Thready Qty Per Inch (tpi):         24         Min. Tensile Strength (psi):         180000 pounds per square inch         Countersink Angle:         Between 9.0 degrees and 10.10 degrees         Material:         Iron alloy 660         Surface Treatment:         Passivate         Surface Treatment:         Qa-p.35 federal specification single treatment response         Thread Series Designator:         Urif         Surface Treatment:         Urif         Surface Treatment:         Date:         Surface Treatment:         Qap-35 federal specification single treatment response         Thread Series Designator:         Urif         Suppressional/industrial association standards         Suppressional/industrial association standards	Between 0.577 inches and 0.635 inches
Internal Drive Style: Torque-set ribbed Thread Diameter: 0.312 inches Grip Length: Between 0.552 inches and 0.572 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qa-p-35 federal specification single treatment response Thread Series Designator: Unif Specification Data: 82055-nas2835 professional/industrial association standard	Grip Diameter:
Torque-set ribbedThread Diameter:0.312 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Surface Treatment:PassivateSurface Treatment:Que-S3 federal specification:Que-S3 federal specification single treatment responseThread Series Designator:UnifSpecification Data:Su205-nas2835 professional/industrial association standard	Between 0.3110 inches and 0.3120 inches
Thread Diameter:0.312 inches0.312 inches0.312 inches0.312 inches0.312 inches0.312 inches0.552 inches and 0.572 inches7.1	Internal Drive Style:
0.312 inchesGrip Length:Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Ion alloy 660Surface Treatment:PassivateSurface Treatment:Quep-35 federal specification:Ange-S5 federal specification single treatment responseIngDarjes Steries Designator:UnifSpecification Data:Su205-nas2835 professional/industrial association standard	Torque-set ribbed
Grip Length:Between 0.552 inches and 0.572 inchesFoready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateGurp-35 federal specification single treatment responseIrbread Specification single treatment responseGrace Treatment Specification single treatment responseForead Series Designator:UnifSpecification Data:Bo205-nas2835 professional/industrial association standard	Thread Diameter:
Between 0.552 inches and 0.572 inchesThready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateQuep-35 federal specification single treatment responseThread Series Designator:UnifSpecification Data:Bo205-nas2835 professional/industrial association standard	0.312 inches
Thready Qty Per Inch (tpi):24Min. Tensile Strength (psi):180000 pounds per square inchCountersink Angle:Between 99.0 degrees and 101.0 degreesMaterial:Ion alloy 660Material Specification:Surface Treatment:PassivateSurface Treatment Specification:Q-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:Bozo5-nas2835 professional/industrial association standard	Grip Length:
24 Min. Tensile Strength (psi): 180000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Aq-p-35 federal specification single treatment response Gap-35 federal specification single treatment response Intread Series Designator: Unjf Specification Data:	Between 0.552 inches and 0.572 inches
Min. Tensile Strength (psi):         180000 pounds per square inch         Countersink Angle:         Between 99.0 degrees and 101.0 degrees         Material:         Iron alloy 660         Material Specification:         Ams 5731 assn standard single material response or ams 5737 assn standard single material response         Surface Treatment:         Passivate         Surface Treatment Specification:         Qq-p-35 federal specification single treatment response         Thread Series Designator:         Unjf         Specification Data:         Boco5-nas2835 professional/industrial association standard	Thready Qty Per Inch (tpi):
18000 pounds per square inch Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas2835 professional/industrial association standard	24
Countersink Angle: Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas2835 professional/industrial association standard	Min. Tensile Strength (psi):
Between 99.0 degrees and 101.0 degreesMaterial:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas2835 professional/industrial association standard	180000 pounds per square inch
Material:Iron alloy 660Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas2835 professional/industrial association standard	Countersink Angle:
Iron alloy 660 Material Specification: Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas2835 professional/industrial association standard	Between 99.0 degrees and 101.0 degrees
Material Specification:Ams 5731 assn standard single material response or ams 5737 assn standard single material responseSurface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas2835 professional/industrial association standard	Material:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response Surface Treatment: Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas2835 professional/industrial association standard	Iron alloy 660
Surface Treatment:PassivateSurface Treatment Specification:Qq-p-35 federal specification single treatment responseThread Series Designator:UnjfSpecification Data:80205-nas2835 professional/industrial association standard	Material Specification:
Passivate Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas2835 professional/industrial association standard	Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment Specification: Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas2835 professional/industrial association standard	Surface Treatment:
Qq-p-35 federal specification single treatment response Thread Series Designator: Unjf Specification Data: 80205-nas2835 professional/industrial association standard	Passivate
Thread Series Designator:         Unjf         Specification Data:         80205-nas2835 professional/industrial association standard	Surface Treatment Specification:
Unjf Specification Data: 80205-nas2835 professional/industrial association standard	Qq-p-35 federal specification single treatment response
Specification Data: 80205-nas2835 professional/industrial association standard	Thread Series Designator:
80205-nas2835 professional/industrial association standard	Unjf
	Specification Data:
Shelf Life:	80205-nas2835 professional/industrial association standard
	Shelf Life:
N/a	N/a
Unit Of Measure:	Unit Of Measure:

## NSN 5305-01-445-8804

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

