NSN 5305-01-445-8807

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-445-8807 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.438 inches **Fastener Length:** Between 1.548 inches and 1.578 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.577 inches and 0.635 inches **Grip Diameter:** Between 0.3110 inches and 0.3120 inches **Internal Drive Style:** Torque-set ribbed **Thread Diameter:** 0.312 inches **Grip Length:** Between 1.115 inches and 1.135 inches Thready Qty Per Inch (tpi): 24 Min. Tensile Strength (psi): 180000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Material: Iron alloy 660 **Material Specification:** Ma 5731 assn standard single material response or ams 5737 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qqp-35 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas2835 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-445-8807

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0