

View Online at <https://aerobasegroup.com/nsn/5305-01-445-8847>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.498 inches

**Fastener Length:**

Between 1.108 inches and 1.138 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.447 inches and 0.507 inches

**Grip Diameter:**

Between 0.2485 inches and 0.2495 inches

**Single Shear Strength:**

132000 pounds per square inch

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.610 inches and 0.635 inches

**Thread Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

240000 pounds per square inch

**Countersink Angle:**

Between 99.0 degrees and 101.0 degrees

**Special Features:**

Dry film lubricant-threads only

**Material:**

Cobalt comp mp-35-n

**Material Specification:**

Ams 5844 assn standard single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A003b0