NSN 5305-01-446-1334

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-446-1334 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** Between 1.138 inches and 1.168 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.502 inches and 0.511 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches Single Shear Strength: 132000 pounds per square inch **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 0.735 inches and 0.765 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 240000 pounds per square inch **Countersink Angle:** Between 129.0 degrees and 131.0 degrees **Special Features:** Dry film lubricant-threads only Material: Cobalt comp mp-35-n **Material Specification:** Ams 5844 assn standard single material response **Surface Treatment: Passivate Surface Treatment Specification:** Qq-p-35 federal specification single treatment response **Thread Series Designator:**

Unif
Shelf Life:
N/a

NSN 5305-01-446-1334

Close Tolerance Screw - Page 2 of 2



ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A003b0