

View Online at <https://aerobasegroup.com/nsn/5305-01-446-1338>

**Thread Class:**

3a

**Thread Direction:**

Right-hand

**Thread Length:**

0.403 inches

**Fastener Length:**

Between 0.888 inches and 0.920 inches

**Head Style:**

Flat countersunk

**Head Diameter:**

Between 0.502 inches and 0.511 inches

**Grip Diameter:**

Between 0.2490 inches and 0.2495 inches

**Single Shear Strength:**

132000 pounds per square inch

**Internal Drive Style:**

Offset cruciform (torque set)

**Thread Diameter:**

0.250 inches

**Grip Length:**

Between 0.490 inches and 0.510 inches

**Thready Qty Per Inch (tpi):**

28

**Min. Tensile Strength (psi):**

240000 pounds per square inch

**Countersink Angle:**

Between 129.0 degrees and 131.0 degrees

**Special Features:**

Dry film lubricant-threads only

**Material:**

Cobalt comp mp-35-n

**Material Specification:**

Ams 5844 assn standard single material response

**Surface Treatment:**

Passivate

**Surface Treatment Specification:**

Qq-p-35 federal specification single treatment response

**Thread Series Designator:**

Unjf

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0