NSN 5305-01-447-1001

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-447-1001 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.403 inches **Fastener Length:** Between 2.326 inches and 2.356 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.464 inches and 0.507 inches **Grip Diameter:** Between 0.2490 inches and 0.2495 inches **Shank Unthreaded Hole Diameter:** 0.076 inches threads and 0.086 inches threads **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.250 inches **Grip Length:** Between 1.938 inches and 1.948 inches Thready Qty Per Inch (tpi): 28 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Distance From Head Largest Bearing Surface To Shank Hole Center: 2.225 inches threads Material: Titanium alloy uns r56400 **Material Specification:** Ams 4928 assn standard single material response or ams 4967 assn standard single material response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-447-1001

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0