## NSN 5305-01-447-1739

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-447-1739 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: Between 0.180 inches and 0.200 inches **Fastener Length:** Between 0.531 inches and 0.562 inches **Head Style:** Pan **Head Diameter:** Between 0.357 inches and 0.373 inches **Head Height:** Between 0.122 inches and 0.133 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.351 inches and 0.362 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: Between 0.133 inches and 0.143 inches **Internal Drive Style:** Cross recess type ii **Thread Diameter:** 0.190 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel **Material Specification:** Qq-s-763, 300 series military specification single material response **Surface Treatment:** Oxide **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** No Fiig:

A003b0

## NSN 5305-01-447-1739

Externally Relieved Body Screw - Page 2 of 2



Mil-std (military Standard):

spec.