## NSN 5305-01-447-2579

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-447-2579 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 1.492 inches **Fastener Length:** 2.890 inches **Head Style:** Flat chamfer **Head Diameter:** Between 0.550 inches and 0.562 inches **Head Height:** Between 0.368 inches and 0.375 inches **First Diameter From Head:** Between 0.3678 inches and 0.3750 inches **Second Diameter From Head:** 0.280 inches **Third Diameter From Head:** Between 0.1941 inches and 0.2041 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: 1.015 inches Distance From Largest Bearing Surface Of Head To End Of Second Diameter: 1.195 inches Distance From Largest Bearing Surface Of Head To End Of Third Diameter: 1.292 inches **Internal Drive Style:** Hexagon **Thread Diameter:** 0.250 inches Width Across Flats: 0.312 inches Thready Qty Per Inch (tpi): 28 **Externally Relieved Body Diameter Quantity:** Material: Iron alloy 660 **Material Specification:** Ams 5731 assn standard single material response or ams 5737 assn standard single material response

Oxide

**Surface Treatment:** 

## NSN 5305-01-447-2579

Externally Relieved Body Screw - Page 2 of 2



Surface Treatment	Specification:
-------------------	----------------

Mil-c-13924, class 1 military specification single treatment response

**Thread Series Designator:** 

Unjf

Shelf Life:

N/a

**Unit Of Measure:** 

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-13924 spec.