
Hexagon Head Cap Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-447-3369

2a Thread Direction: Right-hand Thread Length: 0.875 inches Fastener Length: 0.875 inches Head Style: Hexagon Head Height: Between 0.084 inches and 0.120 inches Width Between Flats: Between 0.309 inches and 0.312 inches
Right-handThread Length:0.875 inchesFastener Length:0.875 inchesHead Style:HexagonHead Height:Between 0.084 inches and 0.120 inchesWidth Between Flats:
Thread Length:0.875 inchesFastener Length:0.875 inchesHead Style:HexagonHead Height:Between 0.084 inches and 0.120 inchesWidth Between Flats:
0.875 inches Fastener Length: 0.875 inches Head Style: Hexagon Head Height: Between 0.084 inches and 0.120 inches Width Between Flats:
Fastener Length:0.875 inchesHead Style:HexagonHead Height:Between 0.084 inches and 0.120 inchesWidth Between Flats:
0.875 inches Head Style: Hexagon Head Height: Between 0.084 inches and 0.120 inches Width Between Flats:
Head Style: Hexagon Head Height: Between 0.084 inches and 0.120 inches Width Between Flats:
Hexagon Head Height: Between 0.084 inches and 0.120 inches Width Between Flats:
Head Height: Between 0.084 inches and 0.120 inches Width Between Flats:
Between 0.084 inches and 0.120 inches Width Between Flats:
Width Between Flats:
Between 0.309 inches and 0.312 inches
Hole Diameter:
Between 0.041 inches and 0.051 inches
Thread Diameter:
0.190 inches
Hole Quantity:
3
Hole Type:
Drilled
Thready Qty Per Inch (tpi):
32
Hole Configuration Style:
Hexagon flats
Special Features:
Longitudinal hole drilled in top of head 0.109" diameter x 0.750" deep. Magnetic permeability: less than 2.
Material:
Steel comp 316
Material Specification:
Qq-s-763 federal specification single material response
Surface Treatment:
Passivate
Surface Treatment Specification:
Qq-p-35 type 1 or type 2 federal specification single treatment response
Thread Series Designator:
Unf
Shelf Life:
N/a
Unit Of Measure:

NSN 5305-01-447-3369 Hexagon Head Cap Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

