

View Online at <https://aerobasegroup.com/nsn/5305-01-447-4359>

Fastener Length:

Between 3.910 inches and 4.000 inches

Head Diameter:

Between 0.437 inches and 0.491 inches

Internal Drive Style:

Cross recess type 1

Countersink Angle:

Between 80.0 degrees and 82.0 degrees

Nonmachine Thread Diameter:

0.242 inches

Special Features:

Head style: flat countersunk no. A199 from old fig a003a; nonmachine thread style: gimlet point no. C13 from old fig a003a; internal drive location: head

Material:

Steel comp 1010 or steel comp 1012 or steel comp 1015 or steel comp 1016 or steel comp 1017 or steel comp 1018 or steel comp 1019 or steel comp 1020 or steel comp 1021 or steel comp 1022 or steel comp 1108 or steel comp 1109 or steel comp 1110 or steel comp 1115 or steel comp 1116 or steel comp 1117 or steel comp 1118

Surface Treatment:

Cadmium and chromate or zinc and chromate

Surface Treatment Specification:

Qq-p-416, type 2, class 3 federal specification 1st treatment response or mil-c-81562, type 2, class 3 military specification 1st treatment response or astm b633, type 2, class 3 assn standard 2nd treatment response or mil-c-81562, type 2, class 3 military specification 2nd treatment response

Specification Or Standard:

1 type and 2c style

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-81562 spec.