Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-447-8656

Thread Class:
За
Thread Direction:
Right-hand
Thread Length:
0.730 inches
Fastener Length:
2.140 inches
Head Style:
Flat chamfer
Head Diameter:
Between 0.550 inches and 0.562 inches
Head Height:
Between 0.368 inches and 0.375 inches
First Diameter From Head:
Between 0.3678 inches and 0.3750 inches
Second Diameter From Head:
0.280 inches
Third Diameter From Head:
Between 0.2581 inches and 0.2591 inches
Distance From Largest Bearing Surface Of Head To End Of First Diameter:
1.015 inches
Distance From Largest Bearing Surface Of Head To End Of Second Diameter:
1.195 inches
Distance From Largest Bearing Surface Of Head To End Of Third Diameter:
1.297 inches
Internal Drive Style:
Hexagon
Thread Diameter:
0.250 inches
Width Across Flats:
0.312 inches
Thready Qty Per Inch (tpi):
28
Externally Relieved Body Diameter Quantity:
3
Material:
Iron alloy 660
Material Specification:
Ams 5731 assn standard single material response or ams 5737 assn standard single material response
Surface Treatment:

Oxide

Externally Relieved Body Screw - Page 2 of 2



### Surface Treatment Specification:

Mil-c-13924, class 1 military specification single treatment response

# Thread Series Designator:

Unf

Shelf Life:

N/a

# Unit Of Measure:

---

## Demilitarization:

No

Fiig:

A003b0

### Mil-std (military Standard):

Mil-c-13924 spec.