NSN 5305-01-448-0666

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-448-0666 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: Between 0.338 inches and 0.388 inches **Fastener Length:** Between 1.536 inches and 1.566 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.339 inches and 0.381 inches **Grip Diameter:** Between 0.2197 inches and 0.2207 inches **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.190 inches **Grip Length:** Between 1.178 inches and 1.198 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 160000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees Surface Finish: 32.0 microinches threads Material: Steel comp e4340 or steel comp 4140 or steel comp 8740 or steel comp 6150 or steel comp 8735 **Surface Treatment:** Cadmium and chromate **Surface Treatment Specification:** Qq-p-416 type 2 cl 2 federal specification single treatment response **Thread Series Designator:** Unjf **Specification Data:** 80205-nas1580 professional/industrial association standard Shelf Life: N/a

Unit Of Measure:

NSN 5305-01-448-0666

Close Tolerance Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0