NSN 5305-01-448-2847

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-448-2847 **Thread Class:** За **Thread Direction:** Right-hand Thread Length: 0.528 inches **Fastener Length:** Between 0.951 inches and 0.981 inches **Head Style:** Flat countersunk **Head Diameter:** Between 0.825 inches and 0.890 inches **Shoulder Diameter:** 0.4516 inches first shoulder and 0.4526 inches first shoulder **Shoulder Length:** 0.428 inches first shoulder and 0.448 inches first shoulder **Internal Drive Style:** Offset cruciform (torque set) **Thread Diameter:** 0.4375 inches Thready Qty Per Inch (tpi): 20 Min. Tensile Strength (psi): 220000 pounds per square inch **Countersink Angle:** Between 99.0 degrees and 101.0 degrees **Shoulder Shape:** Round first shoulder Material: Steel comp e4340 **Material Specification:** Ams 6487 assn standard single material response **Surface Treatment:** Cadmium **Surface Treatment Specification:** Nas 672 assn standard single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure:**

--

NSN 5305-01-448-2847

Shoulder Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0