
Socket Head Cap Screw - Page 1 of 1





| Thread Class:   |
|---|
| 2a  |
| Thread Direction:   |
| Right-hand  |
| Thread Length:  |
| 0.411 inches  |
| Fastener Length:  |
| Between 0.720 inches and 0.750 inches                     |
| Head Style:   |
| Flat countersunk  |
| Head Diameter:  |
| Between 0.600 inches and 0.656 inches                     |
| Locking Feature:  |
| Pellet threads  |
| Internal Drive Style:                                     |
| Hexagon   |
| Thread Diameter:  |
| 0.312 inches  |
| Width Across Flats:                                       |
| 0.188 inches  |
| Thready Qty Per Inch (tpi):                               |
| 18  |
| Countersink Angle:  |
| Between 80.0 degrees and 84.0 degrees                     |
| Material:   |
| Plastic polyamide locking feature                         |
| Material Specification:                                   |
| Astm f468 assn standard single material response fastener |
| Thread Series Designator:                                 |
| Unc   |
| Departure From Cited Document:                            |
| As modified by locking feature                            |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A003b0  |
|   |