NSN 5305-01-448-6195

Close Tolerance Screw - Page 1 of 2

3a

View Online at https://aerobasegroup.com/nsn/5305-01-448-6195



Thread Class: Thread Direction: Right-hand Thread Length: Between 0.345 inches and 0.395 inches Fastener Length: Between 0.980 inches and 1.000 inches **Head Style:** Pan **Head Diameter:** Between 0.473 inches and 0.492 inches **Head Height:** Between 0.162 inches and 0.175 inches **Grip Diameter:** Between 0.2485 inches and 0.2495 inches **Internal Drive Style:** Cross recess type 1 **Thread Diameter:** 0.250 inches Grip Length: Between 0.615 inches and 0.635 inches Thready Qty Per Inch (tpi): Min. Tensile Strength (psi): 160000 pounds per square inch Material: Steel comp e4340 or steel comp 8740 **Material Specification:** Mil-s-6049 military specification 1st material response or ams 6322 assn standard 2nd material response Surface Treatment: Cadmium and chromate **Thread Series Designator:** Unjf **Specification Data:** 80205-nas7704 professional/industrial association standard Shelf Life: N/a Unit Of Measure: **Demilitarization:**

No

28

NSN 5305-01-448-6195

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

Mil-std (military Standard):

Mil-s-6049 spec.

