NSN 5305-01-448-8664

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-448-8664

Thread Class:	
3a	
Thread Direction:	
Right-hand	
Thread Length:	
Between 0.476 inches and 0.526 inches	
Fastener Length:	
Between 1.048 inches and 1.078 inches	
Head Style:	
Flat countersunk	
Head Diameter:	
Between 0.578 inches and 0.634 inches	
Grip Diameter:	
Between 0.3110 inches and 0.3120 inches	
Internal Drive Style:	
Torque-set ribbed	
Thread Diameter:	
0.3125 inches	
Grip Length:	
Between 0.552 inches and 0.572 inches	
Thready Qty Per Inch (tpi):	
24	
Min. Tensile Strength (psi):	
160000 pounds per square inch	
Countersink Angle:	
Between 99.0 degrees and 101.0 degrees	
Material:	
Iron alloy 660	
Material Specification:	
Ams 5731 assn standard single material response or ams	5732 assn standard single material response or ams 5737 assn standard single
material response	
Surface Treatment:	
Passivate	
Surface Treatment Specification:	
Qq-p-35 federal specification single treatment response	
Thread Series Designator:	
Unjf	
Specification Data:	
80205-nas1580 professional/industrial association standard	
Shelf Life:	
N/a	

Unit Of Measure:

NSN 5305-01-448-8664

Close Tolerance Screw - Page 2 of 2

Demilitarization:

No

Fiig:

A003b0

