## NSN 5305-01-449-1909

Shoulder Screw - Page 1 of 2

Between 0.332 inches and 0.403 inches

Between 0.763 inches and 0.793 inches

**Thread Class:** 

Right-hand

Thread Length:

**Thread Direction:** 

Fastener Length:

За



View Online at https://aerobasegroup.com/nsn/5305-01-449-1909

Head Style:
Flat countersunk
Head Diameter:
Between 0.350 inches and 0.399 inches
Shoulder Diameter:
0.2637 inches first shoulder and 0.2643 inches first shoulder
Shoulder Length:
0.312 inches first shoulder
Internal Drive Style:
Offset cruciform (torque set)
Thread Diameter:
0.250 inches
Thready Qty Per Inch (tpi):
28
Min. Tensile Strength (psi):
220000 pounds per square inch
Hardness Rating:
46.0 rockwell c and 50.0 rockwell c
Minimum Yield Strength:
132000 pounds per square inch
Countersink Angle:
99.0 degrees and 101.0 degrees
Shoulder Shape:
Round first shoulder
Material:
Steel comp h11
Material Specification:
Ams 6487 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Nas 672 assn standard single treatment response
Thread Series Designator:
Unjf

## NSN 5305-01-449-1909

Shoulder Screw - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A003b0