NSN 5305-01-449-6992

Panel Screw Assembly - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5305-01-449-6992

Thread Class: 3a **Thread Direction: Right-hand** Fastener Length: Between 1.625 inches and 1.715 inches Head Style: Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.297 inches and 0.327 inches **Internal Drive Style:** Slot **Material Accommodated Thickness:** Between 0.126 inches and 0.187 inches **Thread Diameter:** 0.190 inches Nonstandard Thread Pitch Diameter: +0.1670/+0.1697 inches

Thready Qty Per Inch (tpi):

32

Min. Tensile Strength (psi):

190000 pounds per square inch

Hardness Rating:

375.0 brinell standard fastener and 461.0 brinell standard fastener

Material:

Steel

Material Specification:

Ams 5643, 17-4 cres assn standard single material response

Surface Treatment:

Passivate

Surface Treatment Specification:

Qq-p-35 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

NSN 5305-01-449-6992

Panel Screw Assembly - Page 2 of 2

Fiig:

A003b0

Mil-std (military Standard):

spec.

