NSN 5305-01-449-6992

Panel Screw Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-449-6992 **Thread Class:** За **Thread Direction:** Right-hand Fastener Length: Between 1.625 inches and 1.715 inches **Head Style:** Hexagon **Head Height:** Between 0.105 inches and 0.120 inches Width Between Flats: Between 0.297 inches and 0.327 inches **Internal Drive Style:** Slot **Material Accommodated Thickness:** Between 0.126 inches and 0.187 inches **Thread Diameter:** 0.190 inches **Nonstandard Thread Pitch Diameter:** +0.1670/+0.1697 inches Thready Qty Per Inch (tpi): 32 Min. Tensile Strength (psi): 190000 pounds per square inch Hardness Rating: 375.0 brinell standard fastener and 461.0 brinell standard fastener Material: Steel **Material Specification:** Ams 5643, 17-4 cres assn standard single material response **Surface Treatment: Passivate**

Surface Treatment Specification: Qq-p-35 military specification single treatment response **Thread Series Designator:** Unjf Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

NSN 5305-01-449-6992

Panel Screw Assembly - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

spec.