

View Online at <https://aerobasegroup.com/nsn/5305-01-449-7948>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

4.492 inches

Fastener Length:

Between 4.531 inches and 4.625 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.617 inches and 0.637 inches

Internal Drive Style:

Torque set

Thread Diameter:

0.3125 inches

Thready Qty Per Inch (tpi):

24

Min. Tensile Strength (psi):

160000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Screw Material:

Steel comp 4140 or steel comp 4340 or steel comp 8740

Screw Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-s-6049 military specification 3rd material response

Screw Surface Treatment:

Cadmium or cadmium and chromate

Screw Surface Treatment Specification:

Qq-p-416 ty ii, cl 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Specification Data:

80205-nas1102 professional/industrial association standard

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A500d0

Mil-std (military Standard):

Mil-s-5626 spec.