

View Online at <https://aerobasegroup.com/nsn/5305-01-450-0726>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

0.403 inches

Fastener Length:

Between 0.951 inches and 0.981 inches

Head Style:

Flat countersunk

Head Diameter:

Between 0.3504 inches and 0.3988 inches

Grip Diameter:

Between 0.3422 inches and 0.3432 inches

Internal Drive Style:

Offset cruciform (torque set)

Thread Diameter:

0.250 inches

Grip Length:

Between 0.553 inches and 0.573 inches

Thready Qty Per Inch (tpi):

28

Min. Tensile Strength (psi):

16000 pounds per square inch

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Material:

Steel comp 4140 or steel comp 8740

Material Specification:

Mil-s-5626 military specification 1st material response or mil-s-5000 military specification 2nd material response or mil-6040 military specification 3rd material response

Surface Treatment:

Cadmium and chromate

Surface Treatment Specification:

Qq-p-416 type 2 class 2 federal specification all treatment responses

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A003b0

Mil-std (military Standard):

Mil-s-5626 spec.