NSN 5305-01-451-6385

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-451-6385

Thread Class: 3a Thread Direction: Right-hand Thread Length: 0.276 inches Fastener Length: 3.276 inches Head Style: Flat countersunk Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length: 3.276 inches
Thread Direction: Right-hand Thread Length: 0.276 inches Fastener Length: 3.276 inches Head Style: Flat countersunk Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Right-hand Thread Length: 0.276 inches Fastener Length: 3.276 inches Head Style: Flat countersunk Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Thread Length: 0.276 inches Fastener Length: 3.276 inches Head Style: Flat countersunk Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
0.276 inches Fastener Length: 3.276 inches Head Style: Flat countersunk Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Fastener Length: 3.276 inches Head Style: Flat countersunk Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
3.276 inches Head Style: Flat countersunk Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Head Style: Flat countersunk Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Flat countersunk Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Head Diameter: 0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
0.280 inches Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Head Height: 0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
0.068 inches Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Grip Diameter: Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Between 0.1625 inches and 0.1635 inches Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Internal Drive Style: Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Cross recess type 1 Thread Diameter: 0.164 inches Grip Length:
Thread Diameter: 0.164 inches Grip Length:
0.164 inches Grip Length:
Grip Length:
3.276 inches
Thready Qty Per Inch (tpi):
32
Countersink Angle:
100.0 degrees
Material:
Steel
Material Specification:
Nas498 assn standard single material response
Surface Treatment:
Cadmium
Surface Treatment Specification:
Qq-p-416, ty2, cl2 federal specification single treatment response
Thread Series Designator:
Unjc
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No

NSN 5305-01-451-6385

Close Tolerance Screw - Page 2 of 2



Fiig:

A003b0