NSN 5305-01-451-9862

Close Tolerance Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-451-9862

| Thread Class:3aThread Direction:Right-handThread Length:0.875 inchesFastener Length:Between 1.376 inches and 1.406 inchesHead Style:Flat countersunkHead Diameter:0.578 inchesGrip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.375 inchesHread Diameter:0.375 inchesGrip Length:0.375 inchesThready Qty Per Inch (tpi):24Countersink Angle:Between 99.0 degrees and 101.0 degreesSpecial Features: |
|--|
| Thread Direction:Right-handThread Length:0.875 inchesFastener Length:Between 1.376 inches and 1.406 inchesHead Style:Flat countersunkHead Diameter:0.578 inchesGrip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.875 inchesThread Diameter:24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| Right-handThread Length:0.875 inchesFastener Length:Between 1.376 inches and 1.406 inchesHead Style:Flat countersunkHead Diameter:0.578 inchesGrip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| Thread Length:0.875 inchesFastener Length:Between 1.376 inches and 1.406 inchesHead Style:Flat countersunkHead Diameter:0.578 inchesGrip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.875 inchesInternal Drive Style:0.875 inchesGrip Length:24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| 0.875 inches Fastener Length: Between 1.376 inches and 1.406 inches Head Style: Flat countersunk Head Diameter: 0.578 inches Grip Diameter: 0.578 inches Between 0.3896 inches and 0.3901 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.375 inches Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Fastener Length:Between 1.376 inches and 1.406 inchesHead Style:Flat countersunkHead Diameter:0.578 inchesGrip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| Between 1.376 inches and 1.406 inchesHead Style:Flat countersunkHead Diameter:0.578 inchesGrip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| Head Style:Flat countersunkHead Diameter:0.578 inchesGrip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| Flat countersunkHead Diameter:0.578 inchesGrip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| Head Diameter:0.578 inchesGrip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| 0.578 inches Grip Diameter: Between 0.3896 inches and 0.3901 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.375 inches Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Grip Diameter:Between 0.3896 inches and 0.3901 inchesInternal Drive Style:Offset cruciform (torque set)Thread Diameter:0.375 inchesGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| Between 0.3896 inches and 0.3901 inches Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.375 inches Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Internal Drive Style: Offset cruciform (torque set) Thread Diameter: 0.375 inches Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Offset cruciform (torque set) Thread Diameter: 0.375 inches Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Thread Diameter:0.375 inchesGrip Length:0.875 inchesThready Qty Per Inch (tpi):24Countersink Angle:Between 99.0 degrees and 101.0 degrees |
| 0.375 inches Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Grip Length: 0.875 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| 0.875 inches Thready Qty Per Inch (tpi): 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Thready Qty Per Inch (tpi): 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| 24 Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Countersink Angle: Between 99.0 degrees and 101.0 degrees |
| Between 99.0 degrees and 101.0 degrees |
| τ τ |
| Special Features: |
| |
| Oversize grip dia |
| Material: |
| Steel comp xm-13 |
| Material Specification: |
| Ams 5629 assn standard single material response |
| Surface Treatment: Passivate |
| |
| Surface Treatment Specification: |
| Qq-p-35 federal specification single treatment response |
| Thread Series Designator: |
| |
| Shelf Life: N/a |
| N/a Unit Of Measure: |
| |
| Demilitarization: |
| No |
| |

NSN 5305-01-451-9862

Close Tolerance Screw - Page 2 of 2

Fiig: A003b0

