NSN 5305-01-452-3583

Shoulder Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-452-3583

Thread Direction:
Right-hand
Thread Length:
8.65 millimeters
Fastener Length:
31.25 millimeters
Head Style:
Flat chamfer
Head Diameter:
Between 12.73 millimeters and 13.00 millimeters
Head Height:
Between 5.32 millimeters and 5.50 millimeters
Shoulder Diameter:
7.951 millimeters first shoulder and 7.987 millimeters first shoulder
Shoulder Length:
19.875 millimeters first shoulder and 20.125 millimeters first shoulder
Internal Drive Style:
Hexagon
Thread Diameter:
6.0 millimeters
Width Across Flats:
4.0 millimeters
Min. Tensile Strength (psi):
1100 megapascals
Hardness Rating:
36.0 rockwell c and 43.0 rockwell c
Thread Pitch In Millimeters:
1.0
External Thread Tolerance Class:
4h6h
Shoulder Shape:
Round first shoulder
Special Features:
Shoulder and threads undercut for relief
Material:
Steel
Surface Treatment:
Zinc and chromate
Surface Treatment Specification:
Astm b633 type 2 assn standard single treatment response
Thread Series Designator:

NSN 5305-01-452-3583

Shoulder Screw - Page 2 of 2



_					
•	n	0 1	•	12	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0