

View Online at <https://aerobasegroup.com/nsn/5305-01-452-7240>

**Thread Class:**

2a

**Thread Direction:**

Right-hand

**Thread Length:**

0.190 inches

**Fastener Length:**

Between 0.485 inches and 0.515 inches

**Head Style:**

Pan

**Head Diameter:**

Between 0.208 inches and 0.226 inches

**Head Height:**

Between 0.111 inches and 0.132 inches

**First Diameter From Head:**

Between 0.090 inches and 1.000 inches

**Distance From Largest Bearing Surface Of Head To End Of First Diameter:**

Between 0.295 inches and 0.325 inches

**Internal Drive Style:**

Slot

**End Application:**

F15s

**Thread Diameter:**

0.138 inches

**Features Provided:**

Dry film lubricant

**Thready Qty Per Inch (tpi):**

32

**Externally Relieved Body Diameter Quantity:**

1

**Product Name:**

Screw, captive

**Material:**

Stainless steel

**Material Specification:**

Mil-w-52263c military specification single material response

**Surface Treatment:**

Passivate

**Thread Series Designator:**

Unc

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A003b0

**Mil-std (military Standard):**

Mil-w-52263c spec.