NSN 5305-01-452-7242

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-452-7242 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.190 inches **Fastener Length:** Between 0.985 inches and 1.015 inches **Head Style:** Pan **Head Diameter:** Between 0.208 inches and 0.226 inches **Head Height:** Between 0.111 inches and 0.132 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.295 inches and 0.325 inches **Internal Drive Style:** Slot **End Application:** F15s **Thread Diameter:** 0.138 inches **Features Provided:** Dry film lubricant Thready Qty Per Inch (tpi): 32 **Externally Relieved Body Diameter Quantity: Product Name:** Screw, captive Material: Stainless steel **Material Specification:** Mil-w-52263c military specification single material response **Surface Treatment: Passivate Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure:**

NSN 5305-01-452-7242

Externally Relieved Body Screw - Page 2 of 2



Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-w-52263c spec.