## NSN 5305-01-452-9035

Externally Relieved Body Screw - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5305-01-452-9035 **Thread Class:** 2a **Thread Direction:** Right-hand Thread Length: 0.375 inches **Fastener Length:** 0.512 inches **Head Style:** Flat fillister **Head Diameter:** Between 0.302 inches and 0.317 inches **Head Height:** Between 0.045 inches and 0.055 inches **First Diameter From Head:** 0.097 inches Distance From Largest Bearing Surface Of Head To End Of First Diameter: Between 0.172 inches and 0.202 inches **Internal Drive Style:** Slot **Thread Diameter:** 0.138 inches Thready Qty Per Inch (tpi): **Externally Relieved Body Diameter Quantity:** 1 Material: Steel comp 303 **Material Specification:** Mil-s-7720, cond a military specification single material response **Surface Treatment:** Oxide **Surface Treatment Specification:** Mil-s-13924, class 2 military specification single treatment response **Thread Series Designator:** Unc Shelf Life: N/a **Unit Of Measure: Demilitarization:** 

No

## NSN 5305-01-452-9035

Externally Relieved Body Screw - Page 2 of 2



Fiig:

A003b0

Mil-std (military Standard):

Mil-s-7720 spec.