

View Online at <https://aerobasegroup.com/nsn/5305-01-453-1651>

Thread Class:

3a

Thread Direction:

Right-hand

Thread Length:

Between 0.382 inches and 0.432 inches

Fastener Length:

Between 0.766 inches and 0.796 inches

Head Style:

Flat countersunk undercut

Head Diameter:

Between 0.3765 inches and 0.3813 inches

Head Height:

Between 0.0439 inches and 0.0459 inches

Grip Diameter:

Between 0.1885 inches and 0.1895 inches

Internal Drive Style:

High-torque

End Application:

F-15s

Thread Diameter:

0.190 inches

Grip Length:

Between 0.302 inches and 0.322 inches

Features Provided:

Cetyl alcohol lubricant and o ring

Thready Qty Per Inch (tpi):

32

Countersink Angle:

Between 99.0 degrees and 101.0 degrees

Surface Finish:

32.0 microinches threads

Material:

Steel comp xm-13

Material Specification:

Ams5629 assn standard single material response

Surface Treatment:

Aluminum and chromate

Surface Treatment Specification:

Mil-c-83488 ty2cl3 military specification single treatment response

Thread Series Designator:

Unjf

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A003b0

Mil-std (military Standard):

Mil-c-83488 spec.